

Dyestone Digiace GE-11 Series

1) Summary :

Dyestone Digiace GE-11 Series is the waterbased pigment ink for Piezo type inkjet for textile. Having the pre-treatment with Dyestone Digiace Faster SA + Ionix SB (by Padding or Spray/Press) on the substrate, the Inkjet printing with Digiace GE-11 Inks can achieve fine print with vivid color and softhand effect.

To further improve the quality, Dyestone Digiace has post-treatment chemicals, Dyestone Digiace Abrasion XF + Dyestone Digiace Fixer XA.

This product can be used for various types of substrate; from textiles/garments to industrial materials.

2) Natures :

Appearance	:	Liquid form in various colors
Viscosity	:	10.0 – 12.0 mPa.s (25degreeC)
Surface Tension	:	30 – 38 mN/m
p H	:	7.0 – 9.0
Flammability	:	None, refer SDS

3) Colors :

Available Colors : Yellow GE-11, Special Magenta GE-11,
Cyan GE-11, Special Black GE-11

4) Process :

White Fabric (various types)
↓
Pre-Treatment (Padding process, essential)
↓
Dry / Baking 150°C x 3 mins.
↓
Inkjet Print (C, M, Y, K)
↓
Dry / Baking 150°C x 3 mins.
↓
Finish

TECHNICAL INFORMATION SHEET

5) N.B.

- ① Storage condition : Temp. lower than 30 deg.C and dark place
- ② When changing the ink system on an Inkjet machine, the whole ink supplying system needs to be flushed / cleaned by “Dyestone Digiace Cleaner ST”.
- ③ If the Baking process is insufficient, it affects the fastnesses; therefore, make sure the curing is stably given properly.

* The above information is based on our lab. condition and without guaranty. Pre-test to check the suitability is a must before actual use.