

Dyestone Digiace Pretreatment W-3F

1. Summary

Dyestone Digiace Pretreatment W-3F is pretreatment agent for colored T-shirts for Dyestone Digiace. By inkjet printing of Dyestone Digiace Series on T-shirts processed with this agent, printed T-shirts with soft texture, high fastness, and high white hiding power, can be obtained.

2. General Nature

Appearance Milky white water soluble liquid

Viscosity Less than 10mPa · s

Ionicity Cationic

Specific Gravity . . . 1.05±0.05 g/m³

3. Treatment Formula

(Cloth to Apply)

Cotton Fiber

(Standard Formula)

Use liquid concentrate (100%) without diluting.

Matsui Shikiso Chemical Co., Ltd.

Head Office

64 Kamikazan Sakuradani-cho, Yamashina-ku

Kyoto, 607-8466 Japan

Tel : 075-594-5612 Fax : 075-594-0829

Engineering Dept.

29 Nishino Rikyu-cho, Yamashina-ku,

(Kariya) Kyoto, 607-8345 Japan

Tel : 075-595-5533 Fax : 075-595-5535

(Recommended Process)

Colored T-Shirts

↓

Pretreatment Spray (250~300 g/m²)

↓

Heat Press (180°C×30sec · 20~30kPa)

↓

IJ Print (White) ※

↓

↓ (W/W is possible)

↓

IJ Print (CMYK 4 Color Print) ※

↓

Heat Press (180°C×30sec · 20~30kPa)

↓

Finish

※For further information of each ink, please see the other brochure.

4. N.B.

- ①Store ink at cool and dark place under 30°C.
- ②Avoid contact with anionic materials as Dyestone Digiace Pretreatment W-3F is cationic.